



SERIE 9 M	TECHNICAL FEATURES
DIESEL ENGINE	FPT NEF 6700 cc, 151 kw (205 hp), 6 cylinder, Turbo intercooler, STAGE V, AdBlue
DRIVE SYSTEM	Hydrostatic on all 4 wheels with differential axle
SPRAY TANK CAPACITY	3500 lt + 5% or 4000 lt + 5%
SUSPENSIONS	Front and rear, active, pneumatic with air compressor + hydraulic suspension system, pneumatic on boom parallelogram
BRAKES	PARKING BRAKE: Electric passive brake at the rear wheels SERVICE BRAKE: Hydraulic, on the front and rear axles
GEAR BOX	Continuously variable electrohydraulic gearbox, 0-40km/h
STEERING SYSTEM	4 steering wheels with 4 steering modes
CAB	Class IV, pressurized, air conditioned, heated, n°2 activated carbon filters and pneumatic driver's seat
COMPUTER	ARAG or TRIMBLE, with or without GPS
CLEARENCE	650 - 700 mm
BOOM	Steel 21 - 24 - 27 - 28 m - Aluminium 24 - 28 - 30 m (optional air assisted kit)
DIMENSIONS	Length: 7800 mm Width: 2550 mm (2700 mm Aluminium) Height: 3700 mm Wheel base: 3180 mm
TARE	7700 - 8100 kg
TYRES	320, 340, 380, 420, 480, 540, 600, 710