



SERIE 9 P	TECHNICAL FEATURES
DIESEL ENGINE	FPT NEF 4500 cc, 125 kw (170 hp), 4 cylinder, Turbo intercooler, STAGE V, AdBlue
DRIVE SYSTEM	Hydrostatic pump, 4-wheel drive, with Poclain hydraulic motors on the wheels
SPRAY TANK CAPACITY	3500 L or 4000 L
SUSPENSIONS	Front and rear active pneumatic with air compressor + hydraulic suspension system, pneumatic on boom parallelogram
BRAKES	PARKING BRAKE: Passive electric brake at the rear wheels SERVICE BRAKE: hydraulic disk brakes at the rear wheels OPT: hydraulic disk brakes at the front wheels
GEAR BOX	Electro-hydraulic, 2-speed (0-18 km/h, 0-40 km/h)
STEERING SYSTEM	4 steering wheels with 4 steering modes
CAB	Class IV, pressurized, air conditioned, heated, n°2 activated carbon filters and pneumatic driver's seat
COMPUTER	ARAG or TRIMBLE, with or without GPS
CLEARENCE	1050 mm
BOOM	Steel 21 - 24 - 27 - 28 (optional air assisted kit) – 30 m - Aluminium 24 - 28 - 30 m (optional air assisted kit)
DIMENSIONS	Length: 7800 mm Width: 2550 mm (2700 mm Aluminium) Height: 3800 mm Wheel base: 3180 mm
TARE	7.300 kg - 7.500 kg
TYRES	300, 320, 340, 380, 420, 480, 540, 600, 710